

# **Offer the Maximum Value** with the Minimum Cost.

# **Always More than You Expect.**

# KRONOS H-46 **BATTERY POWERED TOOL** FOR PLASTIC STRAPPING

Kronos H-46 is a world-class battery powered strapping tool with superior features and performance. It can meet most of the strapping requirements for every application. Kronos H-46 is equipped with German-made brushless DC motor to provide the highest level of accuracy and reliability.

Kronos H-46 battery powered strapping tools are available in 2 different models: •H-46A for light and universal application, tension up to 250 kg •H-46B for heavy industry application, tension up to 400 kg

### Max. Tension Up to 400 kg



15F-1, NO. 17, SEC. 1, CHENGDE ROAD, TAIPEI 103, TAIWAN TEL: 886 2 2555 2515 FAX: 886 2 2555 2516 WEB: www.transpakcorp.com E-mail: transpak@transpak.com.tw

Made in Taiw 05.2018×1000 Subject to revision 



# **Kronos**

#### **Battery Powered Tool for Plastic Strapping**

Kronos H-46 is a world-class battery powered strapping tool. With flexible settings, wide tension range and the ability to accommodate both PP and PET strapping, Kronos H-46 is ideal for a wide range applications in all industries and sectors. Kronos H-46 delivers the highest productivity & performance to meet the customers' packaging needs.

### **Main Features**



#### **Easy Operation**

The operation of H-46 is extremely easy. Automatic mode offers fast one-button operation to complete the strapping process in less than 4 seconds.

Versatile design with auto, semi-auto, manual, and soft modes satisfies various strapping requirements.



#### **Digital Touch Panel**

Quick and easy setting through touch panel for various operation modes, tension force, and sealing time simplify the operation. The digital readout on the panel also shows the battery power level, cycle counter, and error codes.



#### Wide Tension Force Range

Easy tension adjustment on the digital touch panel. Variable tension force from 40 kg to 400 kg makes H-46 suitable for various applications in all industries and sectors like brick, wood, corrugated, paper, logistic, etc.



**Bosch Battery and Charger** 

German Bosch high capacity battery provides up to 415 (for PP) and 320 (for PET) strapping cycles per charge. Rechargeable battery with long battery life up to 1,000 charges.



#### Friction Weld Sealing

The advanced **friction weld sealing** technology guarantees reliable joint and high seal efficiency for both PP and PET strapping. An automatic weld function speeds up cycle time.



### **More Features**

# No adjustment required for different strap thickness

No adjustment is required for different strap thickness and the cooling time will be automatically adjusted according to different tension.

#### **Brushless Motor Technology**

German-made brushless DC motor direct drive technology provides the highest level of accuracy and reliability. The state-of-art technology results in less maintenance and longer life time of the motor.

#### **Robust Housing**

The thick and solid structure provides outstanding impact resistance.

#### Perfect Balance and Ergonomic Design

Ergonomic handle with anti-skid design and well-balanced structure makes operation easy and effortless.

#### **Energy Saving Mode**

Tool would automatically go to sleep mode if the tool sits idle for a while for energy saving purpose.

### **Options**

- Suspension bracket
- Bottom base wearing protection plate

## **Technical Data**

| Model Number    | H-46A  | H-46B   |
|-----------------|--|---|
| Specifications  | Light & Universal<br>application                           | Heavy industry<br>application                 |
| Tension Range   | 40 - 250 kg  | 60 - 400 kg                                   |
| Strap Width     | 11 mm - 13 mm,<br>15 mm - 16 mm                            | 15 mm - 16 mm,<br>19 mm                       |
| Strap Thickness | PP<br>0.55 - 1.05 mm<br>PET<br>0.50 - 1.05 mm              | PP<br>0.75 - 1.30 mm<br>PET<br>0.60 - 1.30 mm |
| Net Weight      | 4.3 kg   | 4.4 kg  |
| Battery         | Bosch Li-lon 18V, 4.0Ah                                    |   |
| Battery Charger | Bosch<br>115V (110V-120V),<br>230V (220V-240V) 50/60Hz 1PH |   |